

## Final datasheet

### XHP™2 module with Trench/Fieldstop IGBT5, emitter controlled 5 diode and NTC / pre-applied thermal interface material

#### Features

- Electrical features
  - $V_{CES} = 1700\text{ V}$
  - $I_{C\text{nom}} = 1800\text{ A} / I_{CRM} = 3600\text{ A}$
  - Extended operating temperature  $T_{vj\text{op}}$
  - High current density
  - Low switching losses
  - Low  $V_{CE,\text{sat}}$
  - $T_{vj,\text{op}} = 175^\circ\text{C}$
- Mechanical features
  - High creepage and clearance distances
  - High power and thermal cycling capability
  - High power density
  - Package with CTI > 600




#### Potential applications

- Motor drives
- Traction drives
- Wind turbines
- High-power converters

#### Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068

#### Description



## Table of contents

	<b>Description</b> .....	1
	<b>Features</b> .....	1
	<b>Potential applications</b> .....	1
	<b>Product validation</b> .....	1
	<b>Table of contents</b> .....	2
<b>1</b>	<b>Package</b> .....	3
<b>2</b>	<b>IGBT, Inverter</b> .....	3
<b>3</b>	<b>Diode, Inverter</b> .....	5
<b>4</b>	<b>NTC-Thermistor</b> .....	6
<b>5</b>	<b>Characteristics diagrams</b> .....	7
<b>6</b>	<b>Circuit diagram</b> .....	12
<b>7</b>	<b>Package outlines</b> .....	13
<b>8</b>	<b>Module label code</b> .....	14
	<b>Revision history</b> .....	15
	<b>Disclaimer</b> .....	16

## 1 Package

**Table 1** Insulation coordination

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	$V_{ISOL}$	RMS, $f = 50$ Hz	4.0	kV
Material of module baseplate			Cu	
Creepage distance	$d_{Creep}$	terminal to heatsink	40.0	mm
Creepage distance	$d_{Creep}$	terminal to terminal	34.0	mm
Clearance	$d_{Clear}$	terminal to heatsink	31.0	mm
Clearance	$d_{Clear}$	terminal to terminal	8.0	mm
Comparative tracking index	$CTI$		> 600	

**Table 2** Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Stray inductance module	$L_{sCE}$			10		nH
Module lead resistance, terminals - chip	$R_{AA'+CC'}$	$T_H = 25$ °C, per switch		0.25		mΩ
Module lead resistance, terminals - chip	$R_{CC'+EE'}$	$T_H = 25$ °C, per switch		0.3		mΩ
Storage temperature	$T_{stg}$		-40		150	°C
Maximum baseplate operation temperature	$T_{BPmax}$				150	°C
Mounting torque for module mounting	$M$	- Mounting according to valid application note	M6, Screw	3	6	Nm
Terminal connection torque	$M$	- Mounting according to valid application note	M3, Screw	0.9	1.1	Nm
			M8, Screw	8	10	
Weight	$G$			1020		g

## 2 IGBT, Inverter

**Table 3** Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Collector-emitter voltage	$V_{CES}$	$T_{vj} = 25$ °C	1700	V
Implemented collector current	$I_{CN}$		1800	A
Continuous DC collector current	$I_{CDC}$	$T_{vj\ max} = 175$ °C $T_H = 45$ °C	1535	A

(table continues...)

**Table 3 (continued) Maximum rated values**

Parameter	Symbol	Note or test condition	Values	Unit
Repetitive peak collector current	$I_{CRM}$	$t_p$ limited by $T_{vj\ op}$	3600	A
Gate-emitter peak voltage	$V_{GES}$		±20	V

**Table 4 Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Collector-emitter saturation voltage	$V_{CE\ sat}$	$I_C = 1800\ A, V_{GE} = 15\ V$	$T_{vj} = 25\ ^\circ C$	1.80	2.25	V
			$T_{vj} = 125\ ^\circ C$	2.20	2.75	
			$T_{vj} = 175\ ^\circ C$	2.40	3.00	
Gate threshold voltage	$V_{GEth}$	$I_C = 58\ mA, V_{CE} = V_{GE}, T_{vj} = 25\ ^\circ C$	5.35	5.80	6.25	V
Gate charge	$Q_G$	$V_{GE} = \pm 15\ V, V_{CC} = 900\ V$		8.25		μC
Internal gate resistor	$R_{Gint}$	$T_{vj} = 25\ ^\circ C$		0.5		Ω
Input capacitance	$C_{ies}$	$f = 100\ kHz, T_{vj} = 25\ ^\circ C, V_{CE} = 25\ V, V_{GE} = 0\ V$		84		nF
Reverse transfer capacitance	$C_{res}$	$f = 100\ kHz, T_{vj} = 25\ ^\circ C, V_{CE} = 25\ V, V_{GE} = 0\ V$		3		nF
Collector-emitter cut-off current	$I_{CES}$	$V_{CE} = 1700\ V, V_{GE} = 0\ V$			10	mA
Gate-emitter leakage current	$I_{GES}$	$V_{CE} = 0\ V, V_{GE} = 20\ V, T_{vj} = 25\ ^\circ C$			400	nA
Turn-on delay time (inductive load)	$t_{don}$	$I_C = 1800\ A, V_{CC} = 900\ V, V_{GE} = \pm 15\ V, R_{Gon} = 0.5\ \Omega$	$T_{vj} = 25\ ^\circ C$	0.190		μs
			$T_{vj} = 125\ ^\circ C$	0.200		
			$T_{vj} = 175\ ^\circ C$	0.210		
Rise time (inductive load)	$t_r$	$I_C = 1800\ A, V_{CC} = 900\ V, V_{GE} = \pm 15\ V, R_{Gon} = 0.5\ \Omega$	$T_{vj} = 25\ ^\circ C$	0.110		μs
			$T_{vj} = 125\ ^\circ C$	0.125		
			$T_{vj} = 175\ ^\circ C$	0.130		
Turn-off delay time (inductive load)	$t_{doff}$	$I_C = 1800\ A, V_{CC} = 900\ V, V_{GE} = \pm 15\ V, R_{Goff} = 3\ \Omega$	$T_{vj} = 25\ ^\circ C$	1.060		μs
			$T_{vj} = 125\ ^\circ C$	1.160		
			$T_{vj} = 175\ ^\circ C$	1.220		
Fall time (inductive load)	$t_f$	$I_C = 1800\ A, V_{CC} = 900\ V, V_{GE} = \pm 15\ V, R_{Goff} = 3\ \Omega$	$T_{vj} = 25\ ^\circ C$	0.160		μs
			$T_{vj} = 125\ ^\circ C$	0.370		
			$T_{vj} = 175\ ^\circ C$	0.510		
Turn-on energy loss per pulse	$E_{on}$	$I_C = 1800\ A, V_{CC} = 900\ V, L_\sigma = 20\ nH, V_{GE} = \pm 15\ V, R_{Gon} = 0.5\ \Omega, di/dt = 14500\ A/\mu s (T_{vj} = 175\ ^\circ C)$	$T_{vj} = 25\ ^\circ C$	330		mJ
			$T_{vj} = 125\ ^\circ C$	490		
			$T_{vj} = 175\ ^\circ C$	615		

(table continues...)

**Table 4 (continued) Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit	
			Min.	Typ.	Max.		
Turn-off energy loss per pulse	$E_{off}$	$I_C = 1800\text{ A}$ , $V_{CC} = 900\text{ V}$ , $L_\sigma = 20\text{ nH}$ , $V_{GE} = \pm 15\text{ V}$ , $R_{Goff} = 3\ \Omega$ , $dv/dt = 1800\text{ V}/\mu\text{s}$ ( $T_{vj} = 175\text{ }^\circ\text{C}$ )	$T_{vj} = 25\text{ }^\circ\text{C}$	550		mJ	
			$T_{vj} = 125\text{ }^\circ\text{C}$	707			
			$T_{vj} = 175\text{ }^\circ\text{C}$	800			
SC data	$I_{SC}$	$V_{GE} \leq 15\text{ V}$ , $V_{CC} = 1000\text{ V}$ , $V_{CEmax} = V_{CES} - L_{sCE} * di/dt$	$t_p \leq 10\ \mu\text{s}$ , $T_{vj} = 175\text{ }^\circ\text{C}$	7100		A	
Thermal resistance, junction to heat sink	$R_{thJH}$	per IGBT, Valid with IFX pre-applied Thermal Interface Material				31.3	K/kW
Temperature under switching conditions	$T_{vj\ op}$				-40	175	$^\circ\text{C}$

### 3 Diode, Inverter

**Table 5 Maximum rated values**

Parameter	Symbol	Note or test condition	Values	Unit	
Repetitive peak reverse voltage	$V_{RRM}$	$T_{vj} = 25\text{ }^\circ\text{C}$	1700	V	
Continuous DC forward current	$I_F$		1800	A	
Repetitive peak forward current	$I_{FRM}$	$t_p = 1\text{ ms}$	3600	A	
$I^2t$ - value	$I^2t$	$t_p = 10\text{ ms}$ , $V_R = 0\text{ V}$	$T_{vj} = 125\text{ }^\circ\text{C}$	730	kA <sup>2</sup> s
			$T_{vj} = 175\text{ }^\circ\text{C}$	650	
Maximum power dissipation	$P_{RQM}$	$T_{vj} = 175\text{ }^\circ\text{C}$	1800	kW	

**Table 6 Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$V_F$	$I_F = 1800\text{ A}$ , $V_{GE} = 0\text{ V}$	$T_{vj} = 25\text{ }^\circ\text{C}$	1.75	2.10	V
			$T_{vj} = 125\text{ }^\circ\text{C}$	1.70	2.05	
			$T_{vj} = 175\text{ }^\circ\text{C}$	1.70	2.05	
Peak reverse recovery current	$I_{RM}$	$V_{CC} = 900\text{ V}$ , $I_F = 1800\text{ A}$ , $V_{GE} = -15\text{ V}$ , $-di_F/dt = 14500\text{ A}/\mu\text{s}$ ( $T_{vj} = 175\text{ }^\circ\text{C}$ )	$T_{vj} = 25\text{ }^\circ\text{C}$	1700		A
			$T_{vj} = 125\text{ }^\circ\text{C}$	2000		
			$T_{vj} = 175\text{ }^\circ\text{C}$	2200		

(table continues...)

**Table 6 (continued) Characteristic values**

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Recovered charge	$Q_r$	$V_{CC} = 900\text{ V}$ , $I_F = 1800\text{ A}$ , $V_{GE} = -15\text{ V}$ , $-di_F/dt =$ $14500\text{ A}/\mu\text{s}$ ( $T_{vj} = 175\text{ °C}$ )	$T_{vj} = 25\text{ °C}$	350		$\mu\text{C}$
			$T_{vj} = 125\text{ °C}$	640		
			$T_{vj} = 175\text{ °C}$	850		
Reverse recovery energy	$E_{rec}$	$V_{CC} = 900\text{ V}$ , $I_F = 1800\text{ A}$ , $V_{GE} = -15\text{ V}$ , $-di_F/dt =$ $14500\text{ A}/\mu\text{s}$ ( $T_{vj} = 175\text{ °C}$ )	$T_{vj} = 25\text{ °C}$	220		mJ
			$T_{vj} = 125\text{ °C}$	410		
			$T_{vj} = 175\text{ °C}$	540		
Thermal resistance, junction to heat sink	$R_{thJH}$	per diode, Valid with IFX pre-applied Thermal Interface Material			52.1	K/kW
Temperature under switching conditions	$T_{vj\text{ op}}$		-40		175	$^{\circ}\text{C}$

## 4 NTC-Thermistor

**Table 7 Characteristic values**


Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rated resistance	$R_{25}$	$T_{NTC} = 25\text{ °C}$		5		k $\Omega$
Deviation of $R_{100}$	$\Delta R/R$	$T_{NTC} = 100\text{ °C}$ , $R_{100} = 493\ \Omega$	-5		5	%
Power dissipation	$P_{25}$	$T_{NTC} = 25\text{ °C}$			20	mW
B-value	$B_{25/50}$	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298,15\text{ K}))]$		3375		K
B-value	$B_{25/80}$	$R_2 = R_{25} \exp[B_{25/80}(1/T_2 - 1/(298,15\text{ K}))]$		3411		K
B-value	$B_{25/100}$	$R_2 = R_{25} \exp[B_{25/100}(1/T_2 - 1/(298,15\text{ K}))]$		3433		K

Note: For an analytical description of the NTC characteristics please refer to AN2009-10, chapter 4

**5 Characteristics diagrams**


**Output characteristic (typical), IGBT, Inverter**

$I_C = f(V_{CE})$   
 $V_{GE} = 15\text{ V}$




**Output characteristic field (typical), IGBT, Inverter**

$I_C = f(V_{CE})$   
 $T_{vj} = 175\text{ °C}$




**Transfer characteristic (typical), IGBT, Inverter**

$I_C = f(V_{GE})$   
 $V_{CE} = 20\text{ V}$



**Gate charge characteristic (typical), IGBT, Inverter**

$V_{GE} = f(Q_G)$   
 $I_C = 1800\text{ A}, T_{vj} = 25\text{ °C}$




5 Characteristics diagrams

**Capacity characteristic (typical), IGBT, Inverter**

$C = f(V_{CE})$


$f = 100 \text{ kHz}, V_{GE} = 0 \text{ V}, T_{vj} = 25 \text{ }^\circ\text{C}$



**Switching times (typical), IGBT, Inverter**

$t = f(I_C)$


$R_{Goff} = 3 \text{ } \Omega, R_{Gon} = 0.5 \text{ } \Omega, V_{GE} = \pm 15 \text{ V}, V_{CC} = 900 \text{ V}, T_{vj} = 175 \text{ }^\circ\text{C}$



**Switching times (typical), IGBT, Inverter**

$t = f(R_G)$


$V_{GE} = \pm 15 \text{ V}, I_C = 1800 \text{ A}, V_{CC} = 900 \text{ V}, T_{vj} = 175 \text{ }^\circ\text{C}$



**Switching losses (typical), IGBT, Inverter**

$E = f(I_C)$

$R_{Goff} = 3 \text{ } \Omega, R_{Gon} = 0.5 \text{ } \Omega, V_{CC} = 900 \text{ V}, V_{GE} = \pm 15 \text{ V}$






**5 Characteristics diagrams**

**Switching losses (typical), IGBT, Inverter**

$E = f(R_G)$


$I_C = 1800 \text{ A}$ ,  $V_{CC} = 900 \text{ V}$ ,  $V_{GE} = \pm 15 \text{ V}$



**Reverse bias safe operating area (RBSOA), IGBT, Inverter**


$I_C = f(V_{CE})$

$R_{Goff} \geq 3 \Omega$ ,  $V_{GE} = \pm 15 \text{ V}$ ,  $T_{vj} = 175 \text{ °C}$




**Transient thermal impedance, IGBT, Inverter**

$Z_{th} = f(t)$



**Forward characteristic (typical), Diode, Inverter**


$I_F = f(V_F)$



**5 Characteristics diagrams**


**Switching losses (typical), Diode, Inverter**

$E_{rec} = f(I_F)$   
 $V_{CE} = 900\text{ V}, R_{Gon} = R_{Gon}(IGBT)$




**Switching losses (typical), Diode, Inverter**

$E_{rec} = f(R_G)$   
 $V_{CE} = 900\text{ V}, I_F = 1800\text{ A}$




**Safe operating area (SOA), Diode, Inverter**

$I_R = f(V_R)$   
 $T_{vj} = 175\text{ °C}$




**Transient thermal impedance, Diode, Inverter**

$Z_{th} = f(t)$



Temperature characteristic (typical), NTC-Thermistor

$R = f(T_{NTC})$



## 6 Circuit diagram




Figure 1

## 7 Package outlines




Figure 2

## 8 Module label code



Module label code			
Code format	Data Matrix	Barcode Code128	
Encoding	ASCII text	Code Set A	
Symbol size	16x16	23 digits	
Standard	IEC24720 and IEC16022	IEC8859-1	
Code content	<i>Content</i>	<i>Digit</i>	<i>Example</i>
	Module serial number	1 - 5	71549
	Module material number	6 - 11	142846
	Production order number	12 - 19	55054991
	Date code (production year)	20 - 21	15
	Date code (production week)	22 - 23	30
Example	 		
	71549142846550549911530		71549142846550549911530

Figure 3

## Revision history

Document revision	Date of release	Description of changes
0.10	2022-03-17	Initial version
0.20	2022-12-12	Preliminary datasheet
1.00	2023-10-30	Final datasheet

## Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

**Edition 2023-10-30**

**Published by**

**Infineon Technologies AG**

**81726 Munich, Germany**

**© 2023 Infineon Technologies AG**

**All Rights Reserved.**

**Do you have a question about any aspect of this document?**

**Email: [erratum@infineon.com](mailto:erratum@infineon.com)**

**Document reference**

**IFX-ABD700-003**

## Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.

## Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.