




# ) Modules MDx-660-18-A2



Average forward current				$I_{FAV}$	660 A			
Repetitive peak reverse voltage				$V_{RRM}$	1000...1800 V			
$V_{RRM}, V$	1000	1100	1200	1300	1400	1500	1600	1800
Voltage code	10	11	12	13	14	15	16	18
$T_j, ^\circ C$	-40...+150							



## MAXIMUM ALLOWABLE RATINGS


Symbols and parameters		Units	Values	Test conditions	
<b>ON-STATE</b>					
$I_{FAV}$	Maximum allowable average forward current	A	660	$T_c=100\text{ }^\circ\text{C}$ ; 180° half-sine wave; 50 Hz	
$I_{FRMS}$	RMS forward current	A	1036		
$I_{FSM}$	Surge forward current	kA	19.0 22.0	$T_j=T_{j\max}$ $T_j=25\text{ }^\circ\text{C}$	180° half-sine wave; $t_p=10\text{ ms}$ ; single pulse; $V_R=0\text{ V}$ ;
			20.0 23.0	$T_j=T_{j\max}$ $T_j=25\text{ }^\circ\text{C}$	180° half-sine wave; $t_p=8.3\text{ ms}$ ; single pulse; $V_R=0\text{ V}$ ;
$I^2t$	Safety factor	$A^2s\cdot 10^3$	1800 2400	$T_j=T_{j\max}$ $T_j=25\text{ }^\circ\text{C}$	180° half-sine wave; $t_p=10\text{ ms}$ ; single pulse; $V_R=0\text{ V}$ ;
			1600 2100	$T_j=T_{j\max}$ $T_j=25\text{ }^\circ\text{C}$	180° half-sine wave; $t_p=8.3\text{ ms}$ ; single pulse; $V_R=0\text{ V}$ ;
<b>BLOCKING</b>					
$V_{RRM}$	Repetitive peak reverse voltages	V	1000...1800	$T_{j\min} < T_j < T_{j\max}$ ; 180° half-sine wave; 50 Hz;	
$V_{RSM}$	Non-repetitive peak reverse voltages	V	1100...1900	$T_{j\min} < T_j < T_{j\max}$ ; 180° half-sine wave; single pulse;	
$V_R$	Reverse continuous voltages	V	$0.6\cdot V_{RRM}$	$T_j=T_{j\max}$ ;	
<b>THERMAL</b>					
$T_{stg}$	Storage temperature	$^\circ\text{C}$	-40...+50		
$T_j$	Operating junction temperature	$^\circ\text{C}$	-40...+150		
$T_{c\text{ op}}$	Operating temperature	$^\circ\text{C}$	-40...+125		
<b>MECHANICAL</b>					
a	Acceleration under vibration	$\text{m/s}^2$	50		

## CHARACTERISTICS

Symbols and parameters		Units	Values	Conditions	
<b>ON-STATE</b>					
$V_{FM}$	Peak forward voltage, max	V	1.40	$T_j=25\text{ }^\circ\text{C}$ ; $I_{FM}=1978\text{ A}$	
$V_{F(TO)}$	Forward threshold voltage, max	V	0.78	$T_j=T_{j\max}$ ; $0.5\pi I_{FAV} < I_T < 1.5\pi I_{FAV}$	
$r_T$	Forward slope resistance, max	$\text{m}\Omega$	0.230		
<b>BLOCKING</b>					
$I_{RRM}$	Repetitive peak reverse current, max	mA	50 3.00	$T_j=T_{j\max}$ $T_j=25\text{ }^\circ\text{C}$	$V_R=V_{RRM}$
<b>SWITCHING</b>					
$Q_{rr}$	Total recovered charge, max	$\mu\text{C}$	1750	$T_j=T_{j\max}$ ; $I_{TM}=660\text{ A}$ ; $di_R/dt=-10\text{ A}/\mu\text{s}$ ; $V_R=100\text{ V}$	
$t_{rr}$	Reverse recovery time, max	$\mu\text{s}$	24		
$I_{rr}$	Reverse recovery current, max	A	146		
<b>THERMAL</b>					
$R_{thjc}$	Thermal resistance, junction to case			180° half-sine wave, 50 Hz	
	per module	$^\circ\text{C}/\text{W}$	0.0325		
	per arm	$^\circ\text{C}/\text{W}$	0.0650		
	per module	$^\circ\text{C}/\text{W}$	0.0310		
$R_{thch}$	Thermal resistance, case to heatsink			DC	
	per module	$^\circ\text{C}/\text{W}$	0.0100		
	per arm	$^\circ\text{C}/\text{W}$	0.0200		
<b>INSULATION</b>					
$V_{ISOL}$	Insulation test voltage	kV	3.00	Sine wave, 50 Hz;	$t=60\text{ sec}$
			3.60	RMS	$t=1\text{ sec}$

<b>MECHANICAL</b>				
M <sub>1</sub>	Mounting torque (M6) <sup>1)</sup>	Nm	6.00	Tolerance ± 15%
M <sub>2</sub>	Terminal connection torque (M10) <sup>1)</sup>	Nm	12.00	Tolerance ± 15%
m	Weight, max	g	1500	

<b>PART NUMBERING GUIDE</b>		<b>NOTES</b>
MD	3 - 660 - 18 - A2 - N	<sup>1)</sup> The screws must be lubricated
1	2            3            4            5            6	
1. MD - Rectifier Diode 2. Circuit Schematic: 3 – serial connection 4 – common Cathode 5 – common Anode 3. Average Forward Current, A 4. Voltage Code 5. Package Type (M.A2) 6. Ambient Conditions: N – Normal		




**Fig 1 – On-state characteristics of Limit device**

Analytical function for On-state characteristic:

$$V_F = A + B \cdot i_F + C \cdot \ln(i_F + 1) + D \cdot \sqrt{i_F}$$

	Coefficients for max curves	
	$T_j = 25^\circ\text{C}$	$T_j = T_{j,\text{max}}$
<b>A</b>	0.997101	0.606247
<b>B</b>	0.095326	0.164879
<b>C</b>	-0.153566	-0.217982
<b>D</b>	0.270074	0.383360

**On-state characteristic model (see Fig. 1)**



**Fig 2 – Transient thermal impedance**

Analytical function for Transient thermal impedance junction to case  $Z_{thjc}$  for DC:

$$Z_{thjc} = \sum_{i=1}^n R_i \left( 1 - e^{-\frac{t}{\tau_i}} \right)$$

Where  $i = 1$  to  $n$ ,  $n$  is the number of terms in the series.

$t$  = Duration of heating pulse in seconds.


$Z_{thjc}$  = Thermal resistance at time  $t$ .

$R_i$  = Amplitude of  $p_{th}$  term.


$\tau_i$  = Time constant of  $r_{th}$  term.

$i$	<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>
$R_i$ , K/W	0.0344	0.0112	0.01635	0.0006528	0.001791	0.0001363
$\tau_i$ , s	3.132	1.000	0.2335	0.01038	0.002348	0.0002448


**Transient thermal impedance junction to case  $Z_{thjc}$  model (see Fig. 2)**




**Fig 3 – Total recovered charge,  $Q_{rr-i}$  (integral)**




**Fig 4 - Recovered charge,  $Q_{rr}$  (25% chord)**




**Fig 5 – Peak reverse recovery current,  $I_{rr}$**



**Fig 6 – Maximum recovery time,  $t_{rr}$  (25% chord)**




**Fig 7 – On-state power loss (sinusoidal current waveforms)**




**Fig 8 – On-state power loss (rectangular current waveforms)**







**Fig 9 – Maximum case temperature DSC (sinusoidal current waveforms)**



**Fig 10 – Maximum case temperature DSC (rectangular current waveforms)**



**Fig 11 – Maximum surge and  $I^2t$  ratings**



**Fig 12 – Maximum surge ratings**