



Diode Modules MDx250



AS ENERGI

$I_{F(AV)}$ 250A
 V_{RRM} 600~1800V
 I_{FSM} 9.5 $A \times 10^3$
 I^2t 451A² S $\times 10^3$

Features:

- Isolated mounting base 2500V~
- Pressure contact technology with increased power cycling capability
- Space and weight savings

Typical Applications

- AC/DC Motor drives
- Various rectifiers
- DC supply for PWM inverter

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	$T_J(^{\circ}C)$	VALUE			UNIT
				Min	Type	Max	
$I_{F(AV)}$	Mean forward current	180° half sine wave 50Hz Single side cooled, $T_C=100^{\circ}C$	150			250	A
$I_{F(RMS)}$	RMS forward current		150			393	A
V_{RRM}	Repetitive peak reverse voltage	V_{RRM} tp=10ms $V_{RsM}= V_{RRM}+100V$	150	600		1800	V
I_{RRM}	Repetitive peak current	at V_{RRM}	150			20	mA
I_{FSM}	Surge forward current	10ms half sine wave $V_R=0.6V_{RRM}$	150			9.50	KA
I^2t	I^2T for fusing coordination					451	$A^2s \times 10^3$
V_{FO}	Threshold voltage		150			0.75	V
r_F	Forward slop resistance					0.76	$m\Omega$
V_{FM}	Peak forward voltage	$I_{FM}=750A$	25			1.43	V
$R_{th(j-c)}$	Thermal resistance Junction to case	At 180° sine Single side cooled				0.14	$^{\circ}C /W$
$R_{th(c-h)}$	Thermal resistance case to heatsink	At 180° sine Single side cooled				0.04	$^{\circ}C /W$
V_{iso}	Isolation voltage	50Hz,R.M.S,t=1min, $I_{iso}:1mA(max)$		2500			V
F_m	Terminal connection torque(M8)				12		N·m
	Mounting torque(M6)				6		N·m
T_{stg}	Stored temperature			-40		125	$^{\circ}C$
W_t	Weight				860		g
Outline							




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8

Outline:

