



Thyristor Modules MTx90



$I_{T(AV)}$	90A
V_{DRM}/V_{RRM}	1900~2500V
I_{TSM}	$2.25A \times 10^3$
I^2t	$25A^2 S \times 10^3$

Features:

- Isolated mounting base 3000V~
- Pressure contact technology with Increased power cycling capability
- Space and weight savings

Typical Applications

- AC/DC Motor drives
- Various rectifiers
- DC supply for PWM inverter

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	$T_j(^{\circ}C)$	VALUE			UNIT
				Min	Type	Max	
$I_{T(AV)}$	Mean on-state current	180° half sine wave 50Hz Single side cooled, $T_c=85^{\circ}C$	125			90	A
$I_{T(RMS)}$	RMS on-state current		125			141	A
V_{DRM} V_{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	$V_{DRM} \& V_{RRM}$ tp=10ms $V_{DSM} \& V_{RSM} = V_{DRM} \& V_{RRM} + 100V$ respectively	125	1900		2500	V
I_{DRM} I_{RRM}	Repetitive peak current	at V_{DRM} at V_{RRM}	125			12	mA
I_{TSM}	Surge on-state current	10ms half sine wave	125			2.25	KA
I^2t	I^2T for fusing coordination	$V_R=60\%V_{RRM}$				25	$A^2s \times 10^3$
V_{TO}	Threshold voltage		125			0.85	V
r_T	On-state slop resistance					3.26	$m\Omega$
V_{TM}	Peak on-state voltage	$I_{TM}=270A$	25			1.92	V
dv/dt	Critical rate of rise of off-state voltage	$V_{DM}=67\%V_{DRM}$	125			800	$V/\mu s$
di/dt	Critical rate of rise of on-state current	$I_{TM}=180A$, Gate source 1.5A $t_r \leq 0.5\mu s$ Repetitive	125			100	$A/\mu s$
I_{GT}	Gate trigger current		25	30		100	mA
V_{GT}	Gate trigger voltage	$V_A=12V$, $I_A=1A$		1.0		3.0	V
I_H	Holding current			20		150	mA
V_{GD}	Non-trigger gate voltage	$V_{DM}=67\%V_{DRM}$	125	0.2			V
$R_{th(j-c)}$	Thermal resistance Junction to case	Single side cooled				0.280	$^{\circ}C / W$
$R_{th(c-h)}$	Thermal resistance case to heat sink	Single side cooled				0.15	$^{\circ}C / W$
V_{iso}	Isolation voltage	50Hz,R.M.S,t=1min, $I_{iso}:1mA$ (MAX)	3000				V
F_m	Thermal connection torque (M5)				2.0		$N \cdot m$
	Mounting torque (M6)				3.0		$N \cdot m$
T_{stg}	Stored temperature		-40		125		$^{\circ}C$
W_t	Weight				160		g
Outline							




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8




Fig.9




Fig.10

Outline:

