



High Frequency Thyristor

KG 300A 2000~2400V



- Full diffusion process, distributed extension to amplify the gate structure
- Low switching loss, excellent dynamic characteristic
- Excellent high frequency performances, applicable frequency 2.5-10KHz
- Capsule type ceramic package, double-sided cooling

$I_{T(AV)}$	300A
V_{DRM}/V_{RRM}	2000-2400V
T_q	10-16us
I_{TSM}	3.6KA

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T_J (°C)	VALUE		UNIT
				Min	Max	
$I_{T(AV)}$	Mean on-state current	180° half sine wave 50Hz Double side cooled, THS=55°C	125		300	A
V_{DRM} V_{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	$V_{DRM} \& V_{RRM}$ tp=10ms $V_{DSM} \& V_{RSM}=V_{DRM} \& V_{RRM}+100V$	125	2000	2400	V
I_{DRM} I_{RRM}	Repetitive peak current	$V_{DM}=V_{DRM}$ $V_{RM}=V_{RRM}$	125		40	mA
I_{TSM}	Surge on-state current	10ms half sine wave $V_R=0.6V_{RRM}$	125		3.6	KA
I^2t	I^2t for fusing coordination				168	A^{2S*10}
V_{TO}	Threshold voltage		125		1.67	V
r_T	On-state slop resistance				1.32	$m\Omega$
V_{TM}	Peak on-state voltage	$I_{TM}=900A, F=15KN$	25		3.2	V
dv/dt	Critical rate of rise of-state voltage	$V_{DM}=0.67V_{DRM}$	125		500	V/us
di/dt	Critical rate of rise of on-state current	$V_{DM}=67\%V_{DRM}$ TO 1000A, Gate pulse tr≤0.5us $I_{GM}=1.5A$	125		200	A/us
I_{TM}	Reverse recovery current	$I_{TM}=900A, t_q=1000\mu s$ $Di/dt=-20A/\mu s$. $V_r=50V$	125	30		A
t_{rr}	Reverse recovery time			2.5		us
Q_{rr}	Recovery charge			38	50	uC
t_q	Circuit commutated turn-off time	$I_{TM}=900A, t_q=1000\mu s$, $di/dt=20a/\mu s$ $V_r=50V$	125	10	16	us
I_{GT}	Gate trigger current	$V_A=12V, I_A=1A$	25	30	250	mA
V_{GT}	Gate trigger voltage			0.8	2.5	V
I_H	Holding current			20	400	mA
V_{GD}	Npn-trigger gate voltage	$V_{DM}=0.67V_{DRM}$	125	0.3		V
$R_{th(j-h)}$	Thermal resistance Junction to heat sink	At 180° sine double side cooled Clamping force 5.0kn			0.08	°C/W
F_M	Mounting force				5	KN
T_{stq}	Stored temperature			-40	140	°C
W_t	Weight			0.10		g
Outline						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5





Fig.6

OUTLINE



Dimensions in mm